



EAN code:
PD-1: 8595188193788

Technical parameters	PD-1
Power supply:	2x 1.5 V AA batteries
Battery life:	up to 1 year, according to the number of activations
Drained battery indicator:	yes
Control	
Communication protocol:	RFIO3
Frequency:	866–922 MHz
Repeater function:	no
Detection angle:	110°
Detection distance:	max. 9.5 m
Recommended working height:	max. 2.5 m
Other data	
Working temperature:	-10 to +50 °C
Protection:	IP20
Colour:	black
Dimension:	ø 95mm, height incl. lens 30mm
Weight:	113 g
Related standards:	EN 60730, EN 63044, EN 301489, EN 300 220

- The motion detector PIR is used to detect presence persons moving inside the building interior.
- Use:
 - in combination with a switching unit for automatic control of lighting or triggering an alarm.
 - by means of the Mini Bridge MB-1, detection can be displayed on your smart phone in the form of a notification; alarms are stored in the history, which is visualized in the iNELS Home app.
- Sensitivity settings of the PIR detector for eliminating unwanted triggering.
- Option of activation/deactivation of the LED indicator on the detector cover.
- Power supply: 2x 1.5 V AA batteries, the battery life is around 1 year.
- “Low Battery” Alerts by double LED flashing or on iNELS Home App.
- The detectors are compatible with switching components marked with the RFIO3 communication protocol and the eMini Bridge.

